



# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Revision Date: 02/26/2016 Date of issue: 10/12/2015

Version: 1.2

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Form:** Mixture

**Product Name:** Green Klean GONE

**Product Code:** GK-ORGONE

**Note:** This product, in contact with air or moisture, evolves chlorine dioxide gas. The hazard information for this is contained in section 2.3 and 3. Meets all GHS, OSHA safety guidelines for not exceeding exposure limits of ClO<sub>2</sub> in both the STEL and TWA categories. Note that the component ingredient that is generating the GHS "Danger" warning statement, is in a sealed pouch and workers are at no time exposed to it before, during, or after application. Do Not cut or open sealed inner pouch.

#### Intended Use of the Product

Deodorizer

#### Name, Address, and Telephone of the Responsible Party

SOP Green Klean

615 Industrial Drive, Suite D

Cary, IL 60013

(815)479-0460

[www.gkvacbags.com](http://www.gkvacbags.com)

#### Emergency Telephone Number

**Emergency Number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### GHS-US classification

Comb. Dust

Acute Tox. 4 (Oral) H302

Acute Tox. 3 (Dermal) H311

Acute Tox. 4 (Inhalation: dust,mist) H332

Skin Corr. 1B H314

Eye Dam. 1 H318

STOT RE 2 H373

Full text of H-phrases: see section 16

#### Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)

:



GHS05



GHS08

**Signal Word (GHS-US)** : Do not open inner pouch inside foil pouch.

**Hazard Statements (GHS-US)** : H302+H332 - Harmful if swallowed or if inhaled.

**Precautionary Statements (GHS-US)** : P260 - Do not breathe dust, mist.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection,

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.

# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a poison center or doctor.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see Section 4 on this SDS).  
P330 - Rinse mouth.  
P361 - Take off immediately all contaminated clothing.  
P363 - Wash contaminated clothing before reuse.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Aquatic Acute 1 H400

H400 - Very toxic to aquatic life.

P273 - Avoid release to the environment.



GHS09

**Note:** This product, in contact with air or moisture, evolves chlorine dioxide gas. The product is designed to generate chlorine dioxide solution when the pouch is placed in specified amount of water. The product design **limits** both the amount of gas generated and the rate of release.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Citric acid	(CAS No) 77-92-9	60 - 80	Combustible Dust Eye Irrit. 2A, H319
Sodium chlorite	(CAS No) 7758-19-2	10 - 20	Ox. Sol. 1, H271 Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Calcium chloride	(CAS No) 10043-52-4	10 - 20	Eye Irrit. 2A, H319

**Note:** This product, in contact with air or moisture, evolves chlorine dioxide gas. The product is designed to generate chlorine dioxide solution when the pouch is placed in specified amount of water. The product design **limits** both the amount of gas generated and the rate of release. The composition for this is below.

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Name	Product Identifier	%	Classification (GHS-US)
Chlorine dioxide	(CAS No) 10049-04-4	100	Ox. Gas 1, H270 Compressed gas, H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. Ventilate the area.

**Skin Contact:** Immediately flush skin with plenty of water for at least 60 minutes; Remove contaminated clothing; Immediately call a POISON CENTER or doctor; Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

**Ingestion:** Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Can cause skin burns and eye damage. Harmful if swallowed. Harmful if inhaled. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed

**Inhalation:** Harmful if inhaled. Repeated or prolonged inhalation may damage lungs.

**Skin Contact:** Toxic in contact with skin. Corrosive.

**Eye Contact:** Can cause serious eye damage.

**Ingestion:** Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** In large concentrations it can causes damage to organs (Spleen) through prolonged or repeated exposure.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical, carbon dioxide (CO<sub>2</sub>), water spray, fog (flooding amounts).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Heavy stream of water may spread fire.

#### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not flammable but will support combustion.

**Explosion Hazard:** Product itself is not explosive but if dust is generated, dust clouds suspended in air can be explosive.

**Reactivity:** SODIUM CHLORITE is self-reactive. The trihydrate crystals of sodium chlorite explode on percussion. Sodium chlorite reacts with acids to form spontaneously explosive chlorine dioxide gas (ClO<sub>2</sub>). If heated above 175 °C, the reaction yields enough heat to become self sustaining. Ammonia with chlorites produces ammonium chlorite, which is a shock-sensitive compound. Finely divided metallic or organic substances, if mixed with chlorites, are highly flammable and may be ignited on friction. A mixture of organic matter and sodium chlorite can be extremely sensitive to heat, impact, or friction. Sodium chlorite reacts very violently with organic materials containing divalent sulfur or with free sulfur (may ignite).

#### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Sodium oxides. Sulfur compounds. Chlorine. Corrosive vapors.

# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe dust or fumes. Keep away from heat, sparks, open flames, hot surfaces – No smoking.

### Environmental Precautions

Prevent entry to sewers and public waters.

### Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures, and incompatible materials. Store locked up.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Combustible materials. May react with moisture. Flammable materials. Organic compounds. Wood. Oils and lubricants. Sulfur compounds.

### Specific End Use(s)

Deodorizer

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Calcium chloride (10043-52-4)		
Ontario	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>

**Note:** This product, in contact with air or moisture, evolves chlorine dioxide gas. The product is designed to generate chlorine dioxide solution when the pouch is placed in specified amount of water. The product design **limits** both the amount of gas generated and the rate of release. The exposure limits for this are contained below.

Chlorine dioxide (10049-04-4)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	0.1 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	0.9 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	0.3 ppm
USA ACGIH	ACGIH TWA (ppm)	0.1 ppm
USA ACGIH	ACGIH STEL (ppm)	0.3 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	0.1 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	0.1 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	0.9 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	0.3 ppm
USA IDLH	US IDLH (ppm)	5 ppm
Alberta	OEL STEL (mg/m <sup>3</sup> )	0.8 mg/m <sup>3</sup>
Alberta	OEL STEL (ppm)	0.3 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>

# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Alberta	OEL TWA (ppm)	0.1 ppm
British Columbia	OEL STEL (ppm)	0.3 ppm
British Columbia	OEL TWA (ppm)	0.1 ppm
Manitoba	OEL STEL (ppm)	0.3 ppm
Manitoba	OEL TWA (ppm)	0.1 ppm
New Brunswick	OEL STEL (mg/m <sup>3</sup> )	0.83 mg/m <sup>3</sup>
New Brunswick	OEL STEL (ppm)	0.3 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.28 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	0.1 ppm
Newfoundland & Labrador	OEL STEL (ppm)	0.3 ppm
Newfoundland & Labrador	OEL TWA (ppm)	0.1 ppm
Nova Scotia	OEL STEL (ppm)	0.3 ppm
Nova Scotia	OEL TWA (ppm)	0.1 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	0.82 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	0.3 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	0.27 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	0.1 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	0.82 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	0.3 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	0.27 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	0.1 ppm
Ontario	OEL STEL (ppm)	0.3 ppm
Ontario	OEL TWA (ppm)	0.1 ppm
Prince Edward Island	OEL STEL (ppm)	0.3 ppm
Prince Edward Island	OEL TWA (ppm)	0.1 ppm
Québec	VECD (mg/m <sup>3</sup> )	0.83 mg/m <sup>3</sup>
Québec	VECD (ppm)	0.3 ppm
Québec	VEMP (mg/m <sup>3</sup> )	0.28 mg/m <sup>3</sup>
Québec	VEMP (ppm)	0.1 ppm
Saskatchewan	OEL STEL (ppm)	0.3 ppm
Saskatchewan	OEL TWA (ppm)	0.1 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	0.9 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	0.3 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	0.1 ppm

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: White powder
Odor	: Chlorine
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available

# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Auto-ignition Temperature</b>	: Not available
<b>Decomposition Temperature</b>	: Not available
<b>Flammability (solid, gas)</b>	: Not available
<b>Lower Flammable Limit</b>	: Not available
<b>Upper Flammable Limit</b>	: Not available
<b>Vapor Pressure</b>	: Not available
<b>Relative Vapor Density at 20 °C</b>	: Not available
<b>Relative Density</b>	: Not available
<b>Specific Gravity</b>	: Not available
<b>Solubility</b>	: Soluble in water
<b>Partition Coefficient: N-Octanol/Water</b>	: Not available
<b>Viscosity</b>	: Not available
<b>Explosive Properties</b>	: Heating may cause a fire or explosion
<b>Explosion Data – Sensitivity to Mechanical Impact</b>	: Not expected to present an explosion hazard due to mechanical impact.
<b>Explosion Data – Sensitivity to Static Discharge</b>	: Static discharge could act as an ignition source.

## SECTION 10: STABILITY AND REACTIVITY

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Overheating. Open flame.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Combustible materials. Flammable materials. Organic compounds. Wood. Oils and Lubricants. Moisture.

**Hazardous Decomposition Products:** Thermal decomposition generates : Corrosive vapors. Chlorine. Sodium oxides. Sulfur compounds. Carbon oxides (CO, CO<sub>2</sub>).

### Persistence and Degradability

<b>Citric acid (77-92-9)</b>	
<b>Persistence and Degradability</b>	Readily biodegradable in water.

### Bioaccumulative Potential

<b>Citric acid (77-92-9)</b>	
<b>Log Pow</b>	-1.72 (at 20 °C)
<b>Calcium chloride (10043-52-4)</b>	
<b>BCF Fish 1</b>	(no bioaccumulation)

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 11: DISPOSAL CONSIDERATIONS

**Sewage Disposal Recommendations:** This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Ecology – Waste Materials:** Hazardous waste due to toxicity.

## SECTION 12: REGULATORY INFORMATION

### US Federal Regulations

<b>Green Klean Gone</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Delayed (chronic) health hazard Immediate (acute) health hazard
<b>Sodium chlorite (7758-19-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# Green Klean Gone

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Citric acid (77-92-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard
<b>Calcium chloride (10043-52-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### US State Regulations

#### **Sodium chlorite (7758-19-2)**

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2

RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Chemicals of High Concern  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

#### **Citric acid (77-92-9)**

U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

#### **Calcium chloride (10043-52-4)**

## **SECTION 13: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION**

**Revision Date** : 02/26/2016  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS